

Working Height Max.

Overall Lift Capacity Max.


10 / 8 m (32'10" / 26'3") 230 kg (507 lb) 0.844 m (2'9")

Overall Width
Overall Length
Overall Weight


2.49 m (8'2") 2,200 kg (4,850 lb)

LS0808E Electric Scissor Lift E-Drive

LS0808E SPECIFICATIONS >>>







DIMENOIONO	
DIMENSIONS	
A. Working Height Max. (Indoor/Outdoor)	10 / 8 m (32'10" / 26'3")
B. Platform Height Max. (Indoor/Outdoor)	8 / 6 m (26'3" / 19'8")
C. Platform Height (Stowed)	1.22 m (4')
D. Platform Length	2.28 m (7'6")
E. Platform Width	0.81 m (2'8")
F. Extension Deck (Roll Out)	0.9 m (2'11")
G. Overall Length	2.49 m (8'2")
H. Overall Length (Without Ladder)	2.29 m (7'6")
I. Overall Width	0.844 m (2'9")
J. Stowed Height (Rails Up)	2.36 m (7'9")
K. Stowed Height (Rails Down)	1.8 m (5'11")
L. Wheelbase	1.88 m (6'2")
M. Ground Clearance (Pothole Raised)	100 mm (4")
N. Ground Clearance (Pothole Deployed)	20 mm (0.8")

230 kg (507 lb)
100 kg (220 lb)
2/1
2 km/h (1.2 mph)
0.4 km/h (0.2 mph)
0.24 / 2.2 m (9" / 7'3")
38 / 34 s
25 %
X 1.5° / Y 3°
381 x 127 mm (1'3" x 5")

POWER	
Battery	24 V / 225 Ah
Lithium Battery (Optional)	24 V / 173 Ah
Charger	24 V / 30 A
Lift Motor	24 V / 3.3 kW
Drive Motor	24 V / 0.7 kW
Hydraulic System Volume	23 L (6 gal)
Hydraulic Tank Capacity	20 L (5 gal)

WEIGHT	
Overall Weight	2,200 kg (4,850 lb)